



Technol[®]

Gasoline Conditioner

Product Description Sheet

This state of the art gasoline conditioner, when used once every 3,000 miles, allows the engine to deliver all the power and performance that a clean fuel delivery system was designed to produce.

Technol Gasoline Conditioner will clean accumulated carbons, sticky gums, resin, tar, and varnish deposits from the tank, lines, filters, pumps, injectors/carburetor, combustion chambers, intake and exhaust valves. The properly atomized spray from clean injectors result in increased throttle response, engine power and performance, RPM acceleration, and overall fuel economy. **Technol Gasoline Conditioner** contains a detergent cleaning agent so powerful that it is registered with the EPA as a detergent component for gasoline at the refinery level. Higher octane requirements, and the damaging effects of detonation, pre-ignition, and engine run-on due to “carbon built-up hot spots” within the combustion chambers are reduced as these deposits are eliminated. This reduces fuel related maintenance costs while increasing overall fuel economy. **Technol Gasoline Conditioner's** unique formulation is engineered to improve the ability of today's gasoline to meet the fuel injection cleanliness requirements that are so

important for proper engine operation. Carbureted fuel systems can also receive the same benefits.

Application

Best applied directly to the gas tank before refueling to ensure proper mixing and distribution, but can be added anytime.

Initial Use

Two 8oz Bottles to 11-25 gallons of gasoline. After driving 3,000 miles, follow maintenance use.

Maintenance Use

One 8oz. Bottle treats up to 25 gallons of gasoline once every 3,000 miles city driving, or 5,000 miles highway driving.

This conditioner is designed for ease of use by not having to add to every fill up or top off, and to be available as needed at the pump or on store shelves. This product is not designed for use in bulk storage tanks.

Technol Gasoline Conditioner is available in:

8oz. bottles packed 12 per case
for consumer applications.

5-Gallon Steel Pails
for fleet applications.



Superior Conditioning For Today's Grades of Gasoline

Features & Benefits

*A single use every 3,000 city-driving condition miles
5,000 open-road or highway driving condition miles
or at each scheduled oil change will:*

- Promote easier starting and smoother running
- Improves fuel economy
- Reduce pinging and octane requirement
- Reduces other fuel related maintenance costs
- Use year round to improve fuel economy
- Reduce harmful exhaust emissions
- Cleans fuel tanks, lines, filters, fuel injectors, carburetors, combustion chambers & valves
- Improves horsepower, torque, RPM acceleration, responsiveness, and fuel economy.

Used by and in:

Automobiles ▲ Motorcycles ▲ Boat Owners ▲ Gasoline Trucks

EPA-Approval #1642-0008 for On-Road and Off-Road Use



Technol[®]

Gasoline Conditioner

Technical Data Sheet

Gasoline leaves behind deposits due to evaporation and a lack of stabilization. It evaporates rather easily, and over time, deposits are left in the tank, fuel system, and, after combustion carbon builds-up within the combustion chamber. Harmful detonation, pinging and engine run-on occur when a hot carbon deposit ignites the air/fuel mixture from one side of the combustion chamber **before** the spark plug does. Then the spark plug ignites the other side of the air/fuel mixture.

When these two “flame fronts” meet, a type of “mini explosion” produces “detonation” that cause loss of power, damage pistons, brake piston rings, and other engine components. If you have ever experienced an engine that keeps running after it has been shut off, it is due to the hot carbon deposits that keep igniting the air/fuel mixture.

One way to prevent detonation is to reduce engine timing, which lowers performance. Another way is to use a higher octane gasoline which reduces the fuel’s ability to ignite, but raises fuel costs. The best choice is to remove the deposits.

Technol Gasoline Conditioner used once, every 3,000 miles, will remove these built-up deposits from the entire fuel system, and with continued use will keep the fuel delivery system clean and operating at its power

producing optimum.

Application Directions

Apply directly to the gas tank before refueling to ensure proper mixing and distribution, but can be added anytime.

Initial use

Two 8oz Bottles to 11-20 gallons of gasoline. After driving 3,000 miles, follow maintenance use.

Maintenance use

One 8oz Bottle to 11-20 gallons of gasoline. Once every 3,000 city or 5,000 highway miles.

Normal precautions in the handling of industrial chemicals should be exercised. Skin and eye contact should be avoided. Use only in well-ventilated areas.

Keep this and all other chemical products away from children and animals.

PHYSICAL & CHEMICAL PROPERTIES

MATERIAL IS:	Amber Liquid
APPEARANCE:	Amber
D.O.T.CLASS:	Flammable
FLASH POINT:	100°F (Typical)
DENSITY@25°C:	0.90



Gasoline Conditioner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Rules & Regulations
Revision: 10/06/2017 Issued: 06/01/2000 Supersedes: 04/01/2006

SECTION 1.

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT FORM: Liquid Substance
TRADE NAME: **TECHNOL GASOLINE CONDITIONER**
CHEMICAL NAME: Proprietary mixture of petroleum distillates
COMPANY: Technol Fuel Conditioners, Inc.
145 Wyckoff Road
Eatontown, NJ 07724
Phone: 1.800.645.4033
EPA REGISTRATION: #1642-0008 - Approved for On-Road and Off-Road Fuel Consumption
EMERGENCY PHONE: Chemtrec: 1.800.424.9300 - within USA and Canada
Chemtrec: 1.703.527.3887 - outside USA and Canada

SECTION 2.

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Liquids, 3
Health, Specific target organ toxicity– Single exposure, 3
Health, Acute toxicity, 4 Oral
Health, Acute toxicity, 4 Dermal
Health, Acute toxicity, 4 Inhalation
Health, Skin corrosion/irritation, 1 C
Health, Carcinogenicity, 2
Health, Aspiration hazard, 1
Health, Serious Eye Damage/Eye Irritation, 1

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS HAZARD PICTOGRAMS:



GHS Hazardous Statements:

H226-Flammable liquid and vapor
H335-May cause respiratory irritation
H336-May cause drowsiness or dizziness
H302-Harmful if swallowed
H312-Harmful in contact with skin
H332-Harmful if inhaled
H351-Suspected of causing cancer
H304-May be fatal if swallowed and enters airways
H315-Causes Skin irritation
H320-Causes eye irritation



Gasoline Conditioner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Rules & Regulations
Revision: 10/06/2017 Issued: 06/01/2000 Supersedes: 04/01/2006

GHS Precautionary Statements:

- P210-Keep away from heat/sparks/open flames/hot surfaces. NO SMOKING
- P243-Take precautionary measures against static discharge.
- P233-Keep container tightly closed
- P261-Avoid breathing dust/fume/gas/mist/vapors/spray.
- P301 + 330 + 331-IF SWALLOWED: Rinse mouth. DO NOT induce vomiting
- P302 + 352-IF ON SKIN: Rinse with soap and water.
- P304 + 340- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338-IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P308+313-IF exposed or concerned: Get medical advice/attention.

SECTION 3.

COMPOSITION AND INGREDIENTS INFORMATION

INGREDIENTS:

Cas #	%	Chemical Name
64742-95-6	50-70%	Solvent naphtha, petroleum, light arom.
95-63-6	20-30%	1,2,4-Trimethylbenzene
*****	5-15%	Polyolefin alkyl phenol alkyl ether
111-76-2	<5%	2-Butoxyethanol
1330-20-7	<3%	Xylene

SECTION 4.

FIRST AID MEASURES

- INHALATION:** Overexposure can cause dizziness, lack of coordination, and breathing complications, unlikely to occur under normal usage conditions. Handlers should always wear a self-contained breathing apparatus in the positive mode with a full face-piece due to the likelihood of fumes, smoke, and hazardous component decomposition. Remove to fresh air and deploy artificial respiration if not breathing. Get medical attention.
- SKIN CONTACT:** Can cause irritation of exposed skin due to defatting of skin tissue. Handlers should always wear rubber gloves. Wash exposed skin vigorously with general soap and water. Get medical attention if skin irritation persists.
- EYE CONTACT:** Can cause irritation of exposed eye tissue. Handlers should always wear splash-proof goggles. Rinse eyes with cool flowing water for at least 15 minutes and get immediate medical attention.
- INGESTION:** Can cause irritation of the gastrointestinal tract and possible fatal kidney liver damage. DO NOT INDUCE VOMITING. Deploy artificial respiration if not breathing. Get immediate medical attention.



Gasoline Conditioner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Rules & Regulations

Revision: 10/06/2017 Issued: 06/01/2000 Supersedes: 04/01/2006

SECTION 5. FIREFIGHTING MEASURES

FLASH POINT: 100°F Open Cup (37.8°C), Method = PMCC
LOWER FLAMMABLE LIMIT: % by volume not established
UPPER FLAMMABLE LIMIT: % by volume not established

Special Hazards and Procedures: This product poses no unusual fire fighting problems. It will burn if involved in a fire. Oxides of sulfur (SO₂) will be given off while burning. Combustion may produce oxides of carbon and oxides of calcium. Water may be used to cool fire -exposed containers and structures but is not a suitable extinguishing media.

Protective Equipment: As in any fire, firefighters must be equipped to prevent breathing of vapors or products of combustion. Wear an approved self-contained breathing apparatus and protective clothing.

Extinguishing Media: Dry chemical, CO₂ and foam are suitable. Water jets or any water-based fluid are not suitable. Closed containers may be cooled with water. Treat large fires as an oil fire. Oil will float on water and can cause fire to spread. Heat from fire can generate flammable vapor.

SECTION 6. ACCIDENTAL RELEASE PRECAUTIONS

PERSONAL: Wearing suitable protective equipment, eliminate sources of ignition and open nearby windows to ventilate the problem area.

ENVIRONMENTAL: Product has very low solubility in water. Prevent from entering sewer system, surface water or soil.

FOR SPILL CLEAN-UP: Shut off leak and dike up large spills. Absorb with an inert material such as sand, soil or vermiculite. Sweep up absorbent and dispose in accordance with regulatory requirements.

SECTION 7. PRODUCT HANDLING & STORAGE

HANDLING: This product is best stored in its original container. Steel or HDPE containers are recommended replacements and electrically bond and ground all containers and equipment. Avoid contact with eyes, skin and clothing. Avoid breathing vapors, aerosol and mists. Use with adequate ventilation and wash thoroughly after handling. Never use pressure to empty drums.

STORAGE: Full or partially-filled containers should always be kept upright and away from strong oxidizing agents. This product will pump down to 10°F [-12.2°C]. Nonetheless, it is recommended that full or partially-filled containers be stored in a cool dry place between 45° - 85°F [7.2° - 29.4°C]. Store in original container if possible, and keep all chemical containers away from direct sunlight and tightly closed when not in use.

SECTION 8. EXPOSURE CONTROL/PERSONAL PROTECTION

VENTILATION: None normally required. Use additional ventilation if needed to control vapor concentrations particularly if a mist is generated or fumes from hot material are present.

RESPIRATORY: None required if area adequately ventilated. Use appropriate respiratory protection if used in confined areas. If used in an application where a mist may be generated, observe a TWA/PEL of 5 mg/m³ (OSHA, ACGIH) for a mineral oil mist. Use a respirator with dual organic vapor/mist and particulates cartridge if vapor concentration exceeds permissible exposure limit.

SKIN PROTECTION: Use neoprene-type gloves and apron.

EYE PROTECTION: Wear chemical safety goggles or a full-plate face shield. Contact lenses should not be worn.



Gasoline Conditioner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Rules & Regulations
Revision: 10/06/2017 Issued: 06/01/2000 Supersedes: 04/01/2006

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Amber Liquid	Odor:	Camphor Characteristic
Boiling Point:	300°F [$< 148.9^{\circ}\text{C}$]	Density at 25°C (gm/cm ³):	0.90 Typical
Vapor Pressure:	< 1 @ 20°C (mm Hg)	Vapor density (Air = 1):	Not Determined
Solubility in Water:	Negligible	Solubility in Organic Solvents:	Soluble
pH:	Not Applicable	Flash point, COC (ASTM D-93):	100°F
Pounds per Gallon:	7.5	Evaporation Rate:	< 1 (Butyl Acetate =1)
Freeze Point:	10°F (-12.2°C)	Volatiles By Volume @ 68°F (20°C):	Not Applicable

SECTION 10. STABILITY AND REACTIVITY

This product is stable and not subject to hazardous polymerization.

Hazardous Decomposition Products: Oxides of carbon (carbon monoxide and carbon dioxide), oxides of hydrogen (contaminated and hazardous water), and oxides of Nitrogen can occur when exposed to heat at 350°F (176.7°C).

Incompatible materials: Strong oxidizers such as hydrogen peroxide, oxidizing chlorine, and bromine compounds (e.g. chlorine bleach) and chromic acid should be avoided.

Conditions to avoid: Extreme heat and sources of fire or ignition.

SECTION 11. TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE:	Eye contact, skin contact, inhalation of vapors, and ingestion.
ACUTE TOXICITY:	The handling procedures and safety precautions in this SDS should be followed to minimize employee exposure.
CHRONIC EFFECTS:	Can cause eye, skin and gastrointestinal irritation. Irritation of tissue, defatting of skin, gastrointestinal irritation, Kidney and Liver damage.
SYMPTOMS:	Irritation of exposed tissue and organs, blurriness of vision, dizziness, fainting, and lack of physical coordination.
LD50:	Not Established.
NTP/IARC/OSHA:	This product and none of its components are listed as a carcinogens, mutagens, or teratogens.

SECTION 12. ECOLOGICAL INFORMATION

No specific aquatic data is available. This product should be kept away from all bodies of water, and prevented from entering sewer streams. It may be necessary to extract soil where large spills have occurred. No specific Bioaccumulation data is available. No specific Terrain Migration data is available.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:	This product should be incinerated as a waste oil, at a certified and registered waste disposal site, in compliance with all federal, state and local regulations and requirements.
RCRA STATUS OF rivers,	Dispose of this product in permitted hazardous wastes sites. Keep this product away lakes, streams,
UNUSED PRODUCT:	ponds, sewer systems, and any other body of water.



Gasoline Conditioner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Rules & Regulations
Revision: 10/06/2017 Issued: 06/01/2000 Supersedes: 04/01/2006

SECTION 14. TRANSPORTATION INFORMATION

US DOT Classification:



NA 1993, Combustible Liquid, NOS (placard required on ground carriers): not regulated if shipped or transported in containers less than 450 liters (119 Gallons US).

Proper Shipping Name: Proprietary mixture of petroleum derivatives
Shipping Class: 65 (regardless of package or container size)
Packing Group: III (regardless of package or container size)
NMFC Rating: 155250-02



UN 1993, Flammable Liquid, NOS (placard required on ground carriers): If shipped in containers of 450 liters or more (120 Gallons US or more), by air or by sea.

Proper Shipping Name: Petroleum Distillates, NOS
Shipping Class: 65 (regardless of package or container size)
Packing Group: III (regardless of package or container size)

IMDG Classification:

This product is not known to be a marine pollutant according to the International Marine Dangerous Goods Codes, however it can cause harm to aquatic life.

ICAO Classification:

Proper Shipping Name: Petroleum Distillates, NOS
Class: 3
UN/NA ID #: NA 1993
Packing Group: III

IBC Classification:

Guidance on transporting this product in bulk by ocean freight can be obtained from Annex II of Marpol 73/78 and the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

All Transportation Methods:

Keep packages and containers upright and tightly sealed at all time during transportation. Do not expose packages and containers to direct sunlight, extreme heat, or any source of ignition. All product should be transported in their original packaging and containers. Rubber, plastic or other lined containers should not be used.

SECTION 15. REGULATORY INFORMATION

There are no other national and/or regional statutes or information on this product, including OSHA, Department of Transportation, Environmental Protection Agency, Consumer Product Safety Commission, and Right-To-Know Act not previously addressed in this document.

Chemical Name _____

CAS # _____

NJ TS Number _____

None



Gasoline Conditioner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Rules & Regulations

Revision: 10/06/2017 Issued: 06/01/2000 Supersedes: 04/01/2006

SECTION 16.

OTHER INFORMATION

This product has not been tested in long term, chronic exposure, therefore, the handling procedures and safety precautions in the SDS should be followed to minimize employee exposure.

Label Information for the United States: CAUTION: May cause skin and eye irritation. Do not swallow. Avoid eye and skin contact. Wash thoroughly after handling. Avoid contact with clothing. Wash clothing before reuse. Keep out of reach of children. Keep containers tightly closed when not in use. Avoid breathing mists or sprays of this product or its solutions.

EMPLOYER RESPONSIBILITY

Employers must ensure that these Material Safety Data Sheets are readily accessible and available to all their employees responsible for the storage, handling, and manipulation of this product. This can be done in many ways, such as organizing all chemicals SDS in freely available binders kept in areas where the chemicals are stored, or on computers the handling employees have access to without the inconvenience of leaving the work or storage area. We strongly recommend the binder method which keeps them available in the event of a power outage or other emergency inhibiting computer use. Employers may want to consider designating two persons (primary and backup) responsible for obtaining and maintaining SDS records. If the employer does not have a particular SDS for a chemical commodity, the employer or responsible designate should contact the chemical manufacturer to obtain one prior to product use.

REFERENCES

OSHA, 29 CR 1910.1200(g) and Appendix D.

United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS), 3rd Revised Edition, United Nations, 2009. These references and other information related to the revised Hazard Communication Standard can be found on OSHA's Hazard Communication Safety and Health Topics web site at: <http://www.osha.gov/dsg/hazcom/index.html>.

DISCLAIMER

This brief provides a general overview of the Material Safety Data Sheet requirements as mandated by the Hazard Communication Standard 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200. It does not alter or determine compliance responsibilities in the standard or the Occupational Safety and Health Act of 1970. Since interpretations and enforcement policy may change over time, the reader should consult current OSHA interpretations, decisions by the Occupational Safety and Health Review Commission, and the courts for additional guidance on OSHA compliance requirement. Please note that states with OSHA-approved state plans may have additional requirements for chemical safety data sheets, outside of those outlined above. For more information on those standards, please visit: <http://www.osha.gov/dcsp/osp/statestandards.html>.

The information contained in this document has been derived from analysis of published data freely available and supplied components. While the recommendations contained herein are offered in good faith and believed to be accurate and correct as of the date hereof, manufacturer makes no warranty, expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature regarding this data or the results to be obtained from use thereof. In no event will the manufacturer be liable or responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.



Gasoline Conditioner Application Chart